

XP-3300 / 3000 Series

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	XP-3012H	XP-3312H	XP-3015H	XP-3315H
Processor	Pine View-D SC 1.66 G / 512 K Cache CPU, Upgrade to Pine View -D DC 1.66 G / 1 M Cache CPU (Dual Core)			
System Memory	DDR2 667 MHz, SO-DIMM x 1, max 2 GB, default 1 GB			
Storage Device	2.5" SATA HDD or SSD (optional)			
Power Supply	12V DC power, 80W	12V DC power, 120W	12V DC power, 80W	12V DC power, 120W
Audio	Buzzer Only			
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux			
Display				
LCD	12" TFT LCD, 1024 x 768 resolution		15" TFT LCD, 1024 x 768 resolution	
Touch Function	Resistive, 5-Wire, USB Interface			
Brightness Control	By Digital Push Botton			
Tilt Adjustment	From 14° to 55°			
Connectivity				
LAN Port	10 / 100 / 1000 Mb			
Serial Port	B9 x2, RJ-45x1 (RJ-45 to DB9 Cable Optional), with 5V support on COM2/COM3, 12V support on COM2/COM3			
PS/2 Keyboard	Optional by internal cable			
UPS Port	Yes, Battery Optional			
Standard USB Port	4			
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD Monitor			
CR Port	1, Control 2 CR			
Printer				
3" Thermal Printer	60 mm/sec, 80 mm paper width	150 mm/sec, 80 mm paper width	60 mm/sec, 80 mm paper width	150 mm/sec, 80 mm paper width
Cutter	Auto cutter			
Physical Dimension				
Dimension (W x D x H in mm)	325 X 386.2 X 298.1		375 X 386.2 X 395	
Weight (N. W. in kg)	6.24		6.83	
Environment				
Operation Condition	0°C - 40°C, 20%RH - 90%RH			
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH			
Options				
MSR	Integrated, 2 or 3 tracks or JIS-II			
PD-2606U	VFD, 2 x 20, rear mount			
PD-330U	LCD, 2 x 20, rear mount			
PD-76X4	240 x 64 dot Graphics LCD, default 200 mm pole			
PD-2605 / PD-2605U	VFD, 2 x 20, default 200 mm pole			
PD-309 / PD-309U	LCD, 2 x 20, default 200 mm pole			
SSD	8 G minimum			
LM/TM-2212	12" 2nd LCD Display or touch LCD Display with attachment SD-300			
UPS Battery	2300 mAh / 12V			
Certifications				

XP-3300 / 3000 Series

Advanced All-in-One Fan-Free POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2011 XP33Q1C1

POSIFLEX Posiflex Technology, Inc.
Head Quarter
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

XP-3300 / 3000 Series

Posiflex presents the fan-free XP-3300 / 3000 series as advanced mini POS terminal. The all-in-one POS terminal XP-3300 / 3000 series apply Atom CPU to work efficiently. Offering 1000 Mb Ethernet and plenty of ports such as USB, Serial, VGA and CR, the XP-3300 / 3000 series are advanced in a well-executed design for better operating.

XP-3300 / 3000 series are suitable for small and medium retailers to serve customers efficiently.



Key Features

- ▶ Resistive touch screen : 15" LCD 1280 x 1027 or 12" LCD 1024 x 768 resolution
- ▶ Equipped with the efficient Intel Atom D510 Dual Core 1.66 GHz CPU to lower energy cost
- ▶ All-in-one integrated system with touch screen, thermal printer and MSR for space saving
- ▶ 3" thermal printer with auto cutter
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Aluminum die casting design for efficient cooling
- ▶ Thermal printer with "one-button cutter blade retract" design to clear paper jam easily
- ▶ Special "drop-load" design for easy printer paper roll loading
- ▶ UPS (Embedded on main board developed by Posiflex) support to avoid sudden loss of power during transaction
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ High quality, rock solid design with easy maintenance in mind



Adjustable LCD



with customer pole display



with rear mounted customer display



with MSR and finger print sensor



with 2nd display LCD

Resistive touch screen :
15" or 12" LCD



3" thermal printer with
auto cutter



System and printer status LEDs,
power switch, brightness control
buttons

Fan-free design boasting
quiet and anti-dust features



Built-in magnetic stripe
reader (MSR)(Optional)